

SPECTRO **ARCOS**

ICP-OES ANALYZERS

When
results
matter

SPECTRO **ARCOS**


For the most demanding elemental analyses in industry and research



The new ARCOS analyzer represents a new pinnacle of productivity and performance for inductively coupled plasma optical emission spectrometers. It's a worthy successor to previous industry-leading ARCOS models — as well as the capstone to more than 30 years of SPECTRO experience in producing the world's leading ICP-OES instruments.

SPECTRO ARCOS excels in industrial and academic applications for the most advanced elemental analysis of metals, chemicals, petrochemicals, and other materials. Its unique new MultiView plasma interface option provides truly uncompromising axial-view and radial-view plasma observation in a single instrument. Its innovative, exclusive solid-state generator offers the industry's highest power in an energy-efficient, future-proof package.

Its design ensures exceptionally low operating costs over a long, reliable service life. And it packs a modern, ergonomic chassis with proven features such as no-purge UV-PLUS sealed gas purification technology, no-external-cooling OPI-Air interface, simplified sample introduction, and easy accessibility for service and maintenance. Finally, SPECTRO ARCOS delivers unmatched performance, without any need for added techniques or instruments.



SPECTRO **ARCOS** advantages: analysis without compromise

Revolutionary resolution and sensitivity

SPECTRO ARCOS provides exceptionally high continuous optical resolution over the widest spectral range. This enables easy separation of neighboring lines in line-rich spectra, minimizes spectral interferences, simplifies method development, and improves accuracy. In addition, via direct light paths and other advantages, the system offers the best sensitivity in its class, especially in the VUV/UV range — critical for sub-ppm analyses in metals or in material science applications.

Highest speed

With its fully simultaneous performance, the system can complete a single analysis in as little as 30 seconds. That makes it the fastest in its class. From the simplest sample to the most challenging, SPECTRO ARCOS delivers better analyses at high speed. Result: the user analyzes more samples in less time.

Lowest cost of ownership

SPECTRO ARCOS combines ultra-high performance with an intense focus on long-term cost savings. Examples: patented air-cooled technology eliminates an external chiller with its continuing energy expenses and possible early-replacement costs. And compared to conventional constant-purge designs, its sealed optical system typically saves thousands of dollars annually in gas consumption alone.

Best-in-class stability


Thanks to its uniquely sealed, thermally stabilized optics and extremely robust generator, SPECTRO ARCOS demonstrates superior stability over time. The instrument avoids measurement drift, minimizing reruns and maximizing throughput in process or production control.

Unparalleled ease of use

Every aspect of the system is built for maximum operator safety and ease of use. For example, the plasma torch's bayonet coupling is self-aligning, eliminating the need for optimization after re-installation. The software is simple and intuitive. And connection points and components allow easy front or side access for no-fuss service and maintenance.

Unique flexibility

The system is designed to provide the fastest and most accurate measurement of any sample typically encountered in industrial or research analysis. MultiView gives users the flexibility to choose axial or radial plasma observation according to their desired application profile.



Innovative technologies for spectacular performance

The new SPECTRO ARCOS breaks ground with the introduction of a bold new approach to the heart of any ICP-OES instrument: its plasma viewing interface.

Truly axial, truly radial, truly radical: introducing MultiView

SPECTRO ARCOS revolutionizes spectrometer design with its optional new periscope-free MultiView mechanism. This lets an operator literally “turn” a radial-view instrument into an axial-view device, or vice-versa, in 90 seconds or less!

Consider a user utilizing a MultiView-equipped SPECTRO ARCOS in radial-view mode to analyze major concentrations, who now needs axial view to analyze sub-ppm trace elements in metal matrices. With the few simple steps shown below, the user can access dedicated plasma view performance — without compromises.



1) Simply remove radial torch and interface



2) Rotate load coil into desired horizontal orientation



3) Install axial torch and interface



4) Reconnect sample introduction system

“Dual” view: a question of compromise

High-sensitivity axial plasma observation excels at trace analysis, whereas high-precision radial plasma observation is ideal for analyses requiring compatibility with high matrix loads, and for organic solutions. Until now, dual-view instruments have been the only choice when users require both.


Conventional dual-view designs privilege axial observation with a direct view, adding on radial-view capability via a small periscope.

Unfortunately, this inherently compromises performance. In the radial view, light must encounter multiple mirrors, suffering up to 15% loss of light (and thus information) at every step;

plus, the periscope path cannot be effectively purged. Overall, sensitivity is affected particularly in the UV/VUV range, while stability and precision suffer in case of high matrix loads or organics.

In the end, no periscope-based design can provide the performance available with two dedicated single-view models.

Added Power Range With LDMOS Generator



Ultimate new power source

Plasma power enters a whole new era with the system's innovative generator. This unique component is based on laterally diffused metal oxide semiconductor (LDMOS) technology. SPECTRO ARCOS is the first ICP-OES analyzer to deploy this type of powerful and extremely rugged solid-state generator.

**The results are impressive.
This new generator is**

- **Compact**
- **High-powered**
- **Robust**
- **Energy-efficient**
- **Future-proof**

Superior power

The generator delivers the highest plasma power available today, with a tested and proven range of 500 W to 2000 W. Combined with the system's exclusive optics, these serious power reserves enable previously impossible feats of analysis at the highest plasma loads.

For example, the SPECTRO ARCOS spectrometer can actually analyze volatile organic samples such as gasoline at room temperature!

Yet it's highly energy-efficient. Thanks to the unique SPECTRO ARCOS air-cooled design, the system operates without external cooling, thus achieving low running costs.

Unequaled agility



The generator exhibits high matrix compatibility. Samples can be analyzed in lower dilutions, which results in lower limits of detection.

Additional sample preparation is often not necessary, and specialized techniques such as cooled spray chambers are no longer required.

Longest lifetime

Finally, this generator is extremely robust and trouble-free. Its advanced design is completely short-circuit-proof.

In addition, with no parts subject to wear, the generator minimizes time and expense for maintenance or repair. It's designed to provide excellent uptime and the longest possible service life.



Proven solutions for superiority, simplicity, and savings

Highest-performance optical system [1]

The analyzer's innovative Optimized Rowland Circle Alignment (ORCA) optical technology utilizes few mirrors, providing a direct, high-luminance light path that minimizes light loss.


In addition, SPECTRO ARCOS delivers excellent, constant resolution over a wide spectral range. It's proven to provide the industry's best transparency in the spectral range below 180 nm. This simplifies method development, even in heavy metal matrices, and allows easier processing of line-rich spectra. Result: best-in-class measurement accuracy.

No expensive gas purging [2]

The UV-PLUS sealed optical system is permanently argon-filled, recirculating gas through a small cleaning cartridge good for at least 2 years of life. This eliminates the waste and expense (typically more than \$3000 per year) required by costly conventional designs, which must consume purge gas on a constant basis, and may also risk system contamination by purge gases. It also helps SPECTRO ARCOS achieve high stability and excellent low wavelength performance. So it provides stable analytical results immediately, without purge delays at startup.

No complicated, costly external cooling [3]

SPECTRO produces the only known completely air-cooled ICP-OES analyzer on the market. (All others are water-cooled.) Its unique, innovative OPI-AIR interface saves users from having to buy, install, power, and maintain an elaborate, expensive — and often short-lived — external cooling system.





Ergonomic benchtop design [4]

The system's modernized design fits on any standard laboratory bench, with polyurethane/aluminum construction that's resistant to chemicals and corrosion. Its layout includes thoughtful features such as ultra-short fluid paths. Users enjoy easy, safe accessibility to components from both sides and front for fast, convenient service or maintenance.

Easy, flexible sample introduction system [5]

The spectrometer's thermally insulated, illuminated compartment provides plenty of room to accommodate a large variety of sample introduction systems. Preadjusted setup makes for rapid startup, without the need for comprehensive optimization.




Intuitive interface [6]

A comprehensive Smart Analyzer Vision software package furnishes clear, structured, intuitive control of all functions. It's designed for today's labs, with refined ergonomics and easy LIMS integration. Many routine operations require only a single click. Even analytical method creation is simplified via intelligent assistants/wizards, default settings, and pre-defined templates. Uniquely, the software allows ready reprocessing and recalculation of the full-spectrum data that SPECTRO ARCOS stores with every measurement.

The optional Smart User Interface provides the easiest possible operation — offering manual, prompted manual, or fully automatic analysis — for personnel with minimal training.



COMPREHENSIVE FAMILY



The flagship ARCOS leads SPECTRO's most advanced suite of ICP-OES analyzers.

Included is the SPECTRO GENESIS spectrometer, which sets a new standard for condition monitoring with analysis of wear metal in oil. Available with a complete set of factory-calibrated methods, this ICP-OES provides "plug and analyze" performance, with no need for initial method development. It swiftly and accurately assesses component wear trends, detecting additives, wear elements, and contaminants. Unlike previous ICP analyzers, the innovative SPECTRO GENESIS is easy to use, possesses industrial-grade durability, and is surprisingly affordable to purchase and operate.

Also in the suite is the SPECTROBLUE analyzer, which capitalizes on more than 25 years of benchmark service by SPECTRO inductively coupled plasma optical emission spectrometers. That heritage is highlighted in its Optimized Rowland Circle Alignment (ORCA) optical system, which provides unmatched optical resolution and sensitivity. Engineered for everyday use in industrial or environmental applications, SPECTROBLUE is available in three rugged, ultra-reliable versions, featuring plasma observation in dedicated radial, dedicated axial, or twin interface modes.

Whatever the product, SPECTRO's years of experience in elemental analysis — plus its heritage of technical innovation and excellence — ensure the best possible analytical results.

High-performance services

So that SPECTRO ARCOS spectrometers keep functioning with utmost reliability, SPECTRO offers AMECARE Performance Services. More than 200 service engineers based in over 50 countries help ensure uninterrupted performance as well as maximum ROI over the instrument's life. Available programs include proactive performance maintenance, performance upgrades, applications solutions, consultation, targeted training, and ongoing support. Unique, secure new AMECARE M2M remote monitoring even offers ongoing diagnostics and alerts!



www.spectro.com



GERMANY

SPECTRO Analytical
Instruments GmbH

Boschstrasse 10, D-47533 Kleve

Tel: +49.2821.892.2102

Fax: +49.2821.892.2202

spectro.sales@ametek.com

U.S.A.

SPECTRO Analytical Instruments Inc.
91 McKee Drive

Mahwah, NJ 07430

Tel: +1.800.548.5809

+1.201.642.3000

Fax: +1.201.642.3091

spectro-usa.sales@ametek.com

AMETEK®
MATERIALS ANALYSIS DIVISION

Hong Kong (Asia-Pacific)

SPECTRO Analytical Instruments
(Asia-Pacific) Ltd.

Unit 1603, 16/F., Tower III Enterprise Sq.

No. 9 Sheung Yuet Road

Kowloon Bay, Kowloon

Tel: +852.2976.9162

Fax: +852.2976.9542

spectro-ap.sales@ametek.com

Subsidiaries: ► **CHINA:** Tel +86.10.8526.2111, Fax +86.10.8526.2141, spectro-china.info@ametek.com, ► **FRANCE:** Tel +33.1.3068.8970, Fax +33.1.3068.8999, spectro-france.sales@ametek.com, ► **GREAT BRITAIN:** Tel +44.1162.462.950, Fax +44.1162.740.160, spectro-uk.sales@ametek.com, ► **INDIA:** Tel +91.22.6196.8200, Fax +91.22.2836.3613, sales.spectroindia@ametek.com, ► **ITALY:** Tel +39.02.94693.1, Fax +39.02.94693.650, spectro-italy.sales@ametek.com, ► **JAPAN:** Tel +81.3.6809.2405, Fax +81.3.6809.2410, spectro-japan.info@ametek.co.jp, ► **SOUTH AFRICA:** Tel +27.11.979.4241, Fax +27.11.979.3564, spectro-za.sales@ametek.com, ► **SWEDEN:** Tel +46.8.5190.6031, Fax +46.8.5190.6034, spectro-nordic.info@ametek.com.

► **SPECTRO** operates worldwide and is present in more than 50 countries. For SPECTRO near you, please visit www.spectro.com/worldwide

© 2015 AMETEK Inc., all rights reserved, subject to technical modifications • A-15, Rev. 1 • 80902431 • Photos: SPECTRO, thinkstock, and Getty • Registered trademarks of SPECTRO Analytical Instruments GmbH • **SPECTRO**: USA (3,645,267); EU (005673694); "SPECTRO": EU (009693763); SPECTRO ARCOS: USA (3,451,924); EU (005326566); Japan (5085474); China (5931712)